

WiFi の読み込み

WIFI-COM 受信機の緑と赤の LED ランプが点灯していることを確認してください。



1:お持ちのスマートフォンの設定 からWiFiを受信できるようにON してください。				
<設定	Wi-Fi			
Wi-Fi				
AirDrop、AirPla Wi-Fiが必要です	y、およびより正確な位置† 。	青報を利用するには		



※ WiGET アプリは立ち上げないでください。
現段位では、WiFiの受信がされている状況のみにしてください。











11:Yesをタップ インストールを開始してください。				
← CALIB. UPGRADE ↑				
App Message:				
Calibration Upgrade is ready to start, are you sure?				
No				
TUNING SERVICE MONITOR OPTIONS				







15:MAP2にメールから新たに インストールされたことが確認 できます。				
← SYSTEM INFO				
WIFI module:				
SSID:	WIFICOM-200213150057			
OS Version:	4.4.183-wificom2006			
Srv Version:	0.11.4			
GUI Version:	2006.03			
ECU:				
Fw. Code:	RX1PRO12			
Map Code:	RX1PRO12			
Cns. Code:	RX1PRO06			
Tot. Maps:	03			
APC Map:	APC_YZF250_19PR12r01_034_CL			
Map 1:	YZF250_19PR12r01_041_CLI			
Map 2:	YZF250_19PR12r01_041_CLI			
Device Tag:	IT000RXARX1PR00020190215130			
ATCode	52584152583150524F303047455			
ATCode Burn	52584152583150524F303047455			
TUNING	SERVICE MONITOR OPTIONS			

14:OPTIONSコマンド System Infoをタップ				
ోం	Myl	Bike		
Vehicle Info: Name:		MyBiki	е	
Brand:		ҮАМАНА		
Model:		YZF 250 Other		
Year:		2020		
Other	Š			
My Not	e:		A	
System	Info:			
TUNING	SERVICE	MONITOR	OPTIONS	